

FIG. 1  
PRIOR ART

2/11




FIG. 2




FIG. 3A  
PRIOR ART

34

ORDER	INFORMATION	NOTES
1	TIMESTAMP	
2	BEACON INTERVAL	
3	CAPABILITY INFORMATION	
4	SSID	
5	SUPPORTED RATES	
6	FH PARAMETER SET	THE FH PARAMETER SET INFORMATION ELEMENT IS PRESENT WITHIN PROBE RESPONSE FRAMES GENERATED BY STAs USING FREQUENCY-HOPPING PHYs.
7	DS PARAMETER SET	THE DS PARAMETER SET INFORMATION ELEMENT IS PRESENT WITHIN PROBE RESPONSE FRAMES GENERATED BY STAs USING DIRECT SEQUENCE PHYs.
8	CF PARAMETER SET	THE CF PARAMETER SET INFORMATION ELEMENT IS ONLY PRESENT WITHIN PROBE RESPONSE FRAMES GENERATED BY APs SUPPORTING A PCP.
9	IBSS PARAMETER SET	THE IBSS PARAMETER SET INFORMATION ELEMENT IS ONLY PRESENT WITHIN PROBE RESPONSE FRAMES GENERATED BY STAs IN AN IBSS.




FIG. 3B  
PRIOR ART

36

ORDER	INFORMATION	NOTES
10	NEIGHBOR AP PARAMETER SET	THE TABLE THAT INCLUDES THE CHANNELS NEIGHBOR APs ARE OPERATING ON

FIG. 3C

6/11



7/11




FIG. 5A




FIG. 5B




FIG. 5C




FIG. 6A




FIG. 6B






FIG. 7A

10/11




FIG. 7B




FIG. 7C




FIG. 8A  
PRIOR ART




FIG. 8B  
PRIOR ART




FIG. 8C  
PRIOR ART




FIG. 8D